

depth (incl. stretch)	component	S/N	rope # & Length	Distance from lower rope end	in/out of water comment
1560 m	McLane-12"		#1 15m 1/2" Polyprop	s 3.2t	
1576 m	Billings 3 sphere		#2 1m chain-13	s 3.2t s 3.2t	
1579 m	4x17" glass			shac-link-shac	
1587 m	SBE37 SMP	1500	#3 top 425m 3/16" ins	5/8 Shac Swivel-TI shac-link-shac	
1802 m	SBE37 SMP	1715	#3 bottom		
2008 m	5x17" glass			shac-link-shac	
2013 m	Nortek on load	1930 (estimate)	#4 top 210m 3/16" ins	shac-link-shac	
2018 m	SBE37 SMP	1930	#4 bottom		
2224 m	3x17" glass		#5 top 219m 3/16" ins	shac-link-shac	
2232 m	SBE37 SMP	2145			
2441 m	SBE37 SMP		#5 bottom		

depth (incl. stretch)	component	S/N	rope # & Length	Distance from lower rope end	in/out of water comment
2446 m	2x17" glass			shac-link-shac	
2449 m	ADCP-300-down			shac-link-shac	
2520 m	5x17" glass		#6 70m 3/16" ins	shac-link-shac Swivel-Ti 5/8 Shac	
2525 m	AR-2			shac-link-shac 5/8 Shac	
2546 m	Anchor	900 kg (dry weight) (Wet weight = 783kg) (Safe weight = 670kg)	#7 20m chain-13	3/4 Shac	

