





depth (incl. stretch)	component	S/N	rope # & Length	Distance from lower rope end	in/out of water comment
1298 m	McLane-12"		#1 15m 1/2" Polyprop	s 3.2t	
1315 m	Billings 3 sphere		#2 1m chain-13	s 3.2t s 3.2t	
1317 m	4x17" glass			shac-link-shac	
				5/8 Shac Swivel-TI shac-link-shac	
1326 m	SBE37 SMP	1500	#3 top 575m 3/16" ins		
1616 m	SBE37 SMP	1790			
			#3 bottom		
1897 m	5x17" glass			shac-link-shac	
				shac-link-shac	
1901 m	Nortek on load cell (estimate)	1068	#4 top 285m 3/16" ins	shac-link-shac	
1907 m	SBE37 SMP	2080			
			#4 bottom		
2188 m	3x17" glass			shac-link-shac	
			#5 top 294m 3/16" ins	shac-link-shac	
2195 m	SBE37 SMP	2370			
2480 m	SBE37 SMP		#5 bottom		

depth (incl. stretch)	component	S/N	rope # & Length	Distance from lower rope end	in/out of water comment
2485 m	2x17" glass				
2488 m	ADCP-300-d2000				
2566 m	5x17" glass		#6 77m 3/16" ins		
2571 m	AR-2				
2592 m	Anchor 900 kg (dry weight) (Wet weight = 783kg) (Safe weight = 613kg)		#7 20m chain-13	