

depth (incl. stretch)	component	S/N	rope # & Length	Distance from lower rope end	in/out of water comment
1489 m	McLane-12"			s 3.2t	
			#1 15m 1/2" Polyprop		
1506 m	Billings 3 sphere			s 3.2t s 3.2t	
			#2 1m chain-13		
1508 m	6x17" glass			shac-link-shac	
				5/8 Shac Swivel-T 5/8 Shac	
1514 m	Nortek on load cell (estimate)			shac-link-shac	
			#3 top 675m 3/16" ins		
1520 m	SBE37 SMP	1500			
1860 m	SBE37 SMP	1840			
			#3 bottom		
2191 m	5x17" glass			shac-link-shac	
				shac-link-shac	
2195 m	Nortek on load cell (estimate)			shac-link-shac	
			#4 top 335m 3/16" ins		
2201 m	SBE37 SMP	2180			
			#4 bottom		
2532 m	3x17" glass			shac-link-shac	
				shac-link-shac	
2539 m	SBE37 SMP	2520			
			#5 top 344m 3/16" ins		

depth (incl. stretch)	component	S/N	rope # & Length	Distance from lower rope end	in/out of water comment
2874 m	SBE37 SMP	2520			
			#5 bottom		
2879 m	2x17" glass			shac-link-shac	
				shac-link-shac	
2882 m	ADCP-300-d	2000		shac-link-shac	
			#6 77m 3/16" ins	shac-link-shac	
				shac-link-shac	
2960 m	5x17" glass			shac-link-shac	
				shac-link-shac	
				shac-link-shac	
2965 m	AR-2			shac-link-shac	
			#7 20m chain-13	3/8 Shac	
				3/4 Shac	
2986 m	Anchor	900 kg (dry weight) (Wet weight = 783kg) (Safe weight = 610kg)			