



22 17" Balls in Hard Hats
ON 3/8" Mooring Chain
(5 SETS OF 4, 1 SET OF 2)

50 M. 1/4" Wire Rope

0.5 M. 3/8" Mooring Chain

RAFOS Sound Source
Depth 1200m

0.5 M. 3/8" Mooring Chain

3 Ton Miller Swivel

0.5 M. 3/8" Mooring Chain

ACOUSTIC RELEASE

500 M. 3/16" Wire Rope

300 M. 3/16" Wire Rope

1000 M. 3/8" Yalex Dacron

1000 M. 3/8" Yalex Dacron

50 M. 3/16" Wire Rope

20 M. 3/16" Wire Rope

10 M. 1/4" Wire Rope

5 M. 3/8" Mooring Chain

2,000 LB (Wet Wt.) Anchor

DEPTH =4,200 Meters

TERMINATION CODES	
A	1/2" Anchor Shackle, 5/8" Sling Link, 1/2" Anchor Shackle
B	5/8" Anchor Shackle, 5/8" Sling Link, 1/2" Anchor Shackle
D	7/8" Anchor Shackle, 5/8" Sling Link, 1/2" Anchor Shackle

HARDWARE REQUIRED	
1/2" Anchor Shackles	- 35
5/8" Anchor Shackles	- 6
7/8" Anchor Shackles	- 1
5/8" Sling Links	- 21

EXPORT PATHWAYS EXPERIMENT MOORING "C3"-Revised

G. Tupper - 24 MAY 05
Rev 1 - 17 June 05